

DONGFENG

VL TRACTOR HEAD

6X4 310 HP

BUILT TO PERFORM
READY FOR ANY CHALLENGE



ENGINE



EURO 5

GVW



49.000 KG

HORSE POWER



310 HP

TORQUE



1150 NM

TRANSMISSION



12 GEARS MT

FUEL TANK CAPACITY



350 L



CHASSIS WITH BODY DIMENSION (mm)

Overall Chassis Length	6960
Cab Width	2110
Cab Height (unladen)	3030
Wheel Base	3300+1350
Front Overhang	1500
Rear Overhang	850



CHASSIS WEIGHT (kg)

G.C.W	49000
Curb Weight (chassis)	8870



FRAME PROFILE DIMENSIONS (mm)

Frame Width (front)	940
Frame Width (rear)	850
Section size	280



ENGINE

Type	YC6L 310-50 Engine
Emission level	Euro 5
Max Power	217KW
Max Torque	1150 N.m
Number of Cylinders	6
Displacement (lit)	8.4



GEAR BOX

Type	9JSD135T-B
Gear Ratio	121.118.08.m.964.423.24.21; 1761.132.1.00 Reverse:1266
Fifth Wheel	60#



CAB

Sleeper cab, forward control type, low roof, new face, all welded steel cab of tilt type, electrical cab tilting, all floating mechanical cab suspension, adjustable driver's seat, air conditioning system, electric window, central lock



AXLE

Front Hande Brand	Load capacity (ton) 7
Rear Hande Brand	Load capacity (ton) 5
Gear Ratio	4.33



TYRES

215/75R17.516PR



SUSPENSION

Front	9 Leaf spring
Rear	10 Leaf spring



BATTERY

Voltage (V)	24
Battery Capacity (A.h)	165x2



FUEL TANK

Type	Aluminium alloy tank
Capacity	400 L



BRAKE SYSTEM

Full air brake system, split pneumatic circuit; parking spring brake action on rear axles, exhaust brake, ABS



RELIABLE
PERFORMANCE



HIGH DURABILITY
FOR TOUGH JOBS



FUEL EFFICIENT
MORE PRODUCTIVE



AFTER SALES SUPPORT
SERVICE & SPARE PARTS ORIGINAL